





POWER WASH

A top of the range machine with unbeatable performance, the Powerwash is purpose built for a customer's needs. The 12m Wash Platform offers 4 revolutions of the wheel over sprays and is the **longest standard wash system on the market.** With the right settlement configuration the **Powerwash can clean 1,000 vehicles per day.**

- 12m or 9m Wash Platform options as standard but can be built any size.
- 22kw or 30kw pump options as standard but has been installed with 50kw.
- Up to 200 spray nozzles as standard, customer specific spray patterns are available.
- 52,000 litres of recycling as standard, the highly effective, easy to empty, 3-tank settlement system can be extended infinitely or can be used with customer's own lagoons.
- Wash Platform can be inset in the ground to make entry and exit easier or surface mounted for simple installation.
- At 2.5m the side screens are the highest of any standard wheelwash in production in the world and maximise water retention. Galvanized option available.
- Wide enough to accommodate most Articulated Dump Trucks up to 30 ton.
- Fully adjustable, programmable system for changeable site conditions.
- All spraying products come with removable grids in the Wash Platform as standard. Wheelwash Ltd is the only company in the market to provide this essential feature.
- External waste sump is at lowest point for efficient waste recycling.
- Hand-lance fed from main wash pump with 20m hose as standard.
- 460 mm high wash platform provides a large capacity to cope with heavy traffic.
- 3m ramps provide a soft entry suitable for most vehicle types.
- Heavy-duty steel construction.
- All Wheelwash Ltd products are designed and manufactured in Britain.

Product Specification

POWER WASH



All Dimensions in Millimetres

	9m Powerwash	12m Powerwash
Main Components		
Wash Platform	9000mm x 3500mm x 460mm 7000 Litres Capacity	12000mm x 3500mm x 460mm 9650 Litres Capacity
Ramp (Each & Optional)	3000mm x 1000mm x 460mm 340 Kgs	3000mm x 1000mm x 460mm 340 Kgs
Mobile Road (Each)	3000mm x 1000mm x 460mm 385 Kgs	3000mm x 1000mm x 460mm 385 Kgs
Primary Settlement Tank	2000mm x 2000mm x 3460mm 1870 Kgs 13400 Litres Capacity	2000mm x 2000mm x 3460mm 1870 Kgs 13400 Litres Capacity
Secondary Settlement Tank	8000mm x 2000mm x 2000mm 4470 Kgs 27200 Litres Capacity	8000mm x 2000mm x 2000mm 4470 Kgs 27200 Litres Capacity
Pumphouse & Header Tank	4000mm x 2000mm x 1700mm 2162 Kgs 11200 Litres Capacity	4000mm x 2000mm x 1700mm 2162 Kgs 11200 Litres Capacity
Side Screens (each)	6 Off 2500mm x 3000mm x 2mm 165 Kgs (each)	8 Off 2500mm x 3000mm x 2mm 165 Kgs (each)
Power Supply Required		
Mains Power	415v 80amp Supply D Type Circuit Breaker	415v 80amp Supply D Type Circuit Breaker
Generator	80 kVA	80 kVA
Wash Pump Specification		
Rating (kw)	30	30
Flow Rate (Ltr/ Min)	1675	1675
Pressure (bar)	6.5	6.5
Waste Pump Specification		
Rating (kw)	5.2	5.2
Flow Rate (Ltr/ Min)	1,440	1,440
Handlance		
Hose Length (Metres)	20m	20m
Water Supply / Nozzles		
Water Inlet Required	25mm or 50mm	25mm or 50mm
Spray Nozzles	Up to 150	Up to 150

*All weights are approximate dry weights. Wheelwash Limited reserves the right to change detailed specifications from time to time. Drawings are to show indicative layouts only and are not to scale. Specifications are based on supply within the UK, please ask for details outside of this location. Specifications may vary when systems supplied as rental units.




RHINO MULTI

The UK's most popular model with a **proven worldwide pedigree**, the Rhino Multi is a complete all rounder and **effective in most site conditions**.

Numerous options are available for tailoring this **robust, versatile, market leader** to a customer's needs. .

- 4m or 6m Wash Platform options.
- 22kw or 30kw pump. Combined with the high performance spray configuration the 30kw pump has more pressure than any other standard unit on the market at 6.5 bar.
- 35,000 litres of recycling as standard, with additional upgrades to the highly effective, easy to empty, 3-tank settlement system available.
- Wash Platform can be inset in the ground or truly surface mounted with no excavation required.
- Mobile unit able to be re-located on site in one day.
- At 2.5m the side screens are the highest of any standard wheelwash in production in the world and maximise water retention. Galvanized option available.
- Can be used with customers own settlement lagoons.
- The Rhino Multi is a fully adjustable, programmable system for changeable site conditions.
- All spraying products come with removable grids in the Wash Platform as standard. Wheelwash Ltd is the only company in the market to provide this essential feature.
- Integrated ladder and walkway for access to the tanks as standard.
- Hand-lance fed from main wash pump with 10m hose as standard.
- 380 mm high wash platform provides a soft entry suitable for most vehicle types.
- Hassle free set up with delivery via Hiab crane truck.
- Heavy-duty steel construction.
- All Wheelwash Ltd products are designed and manufactured in Britain.

Product Specification



All Dimensions in Millimetres

	Rhino Multi 4000	Rhino Multi 6000
Main Components		
Wash Platform	4000mm x 3500mm x 380mm 2205 Kgs 2650 Litres Capacity	6000mm x 3500mm x 380mm 3,400 Kgs 4000 Litres Capacity
Ramp (Each & Optional)	3000mm x 1000mm x 380mm 295 Kgs	3000mm x 1000mm x 380mm 295 Kgs
Mobile Road (Each)	3000mm x 1000mm x 380mm 325 Kgs	3000mm x 1000mm x 380mm 325 Kgs
Primary Settlement Tank	2000mm x 2000mm x 3460mm 1,870 Kgs 13400 Litres Capacity	2000mm x 2000mm x 3460mm 1870 Kgs 13400 Litres Capacity
Secondary Settlement Tank	4000mm x 1500mm x 1300mm 1,330 Kgs 8000 Litres Capacity	4000mm x 1500mm x 1300mm 1330 Kgs 8000 Litres Capacity
Pumphouse & Header Tank	4000mm x 2000mm x 1700mm 2,162 Kgs 11200 Litres Capacity	4000mm x 2000mm x 1700mm 2162 Kgs 11200 Litres Capacity
Side Screens (each)	4 Off 2500mm x 2000mm x 2mm 110 Kgs (each)	6 Off 2500mm x 2000mm x 2mm 110 Kgs (each)
Power Supply Required		
Mains Power	415v 63amp Supply D Type Circuit Breaker	415v 80amp Supply D Type Circuit Breaker
Generator	60 kVA	80 kVA
Wash Pump Specification		
Rating (kw)	22	30
Flow Rate (Ltr/ Min)	1650	1675
Pressure (bar)	5.5	6.5
Waste Pump Specification		
Rating (kw)	5.2	5.2
Flow Rate (Ltr/ Min)	1440	1440
Handlance		
Hose Length (Metres)	10m	10m
Water Supply / Nozzles		
Water Inlet Required	25mm or 50mm	25mm or 50mm
Spray Nozzles	Up to 80	Up to 120

*All weights are approximate dry weights. Wheelwash Limited reserves the right to change detailed specifications from time to time. Drawings are to show indicative layouts only and are not to scale. Specifications are based on supply within the UK, please ask for details outside of this location. Specifications may vary when systems supplied as rental units.



RHINO COMPACT


A cost-effective solution, the Rhino Compact is designed for lower volume sites dealing with lighter material but retains the Rhino features of **robustness and versatility**.

A highly effective solution on the correct application, sometimes less is more.

- 4m Wash Platform with high performance spray configuration, longer platforms are available at customer's request.
- 9.4kw as standard with various pump configurations available.
- Only a 30kva generator required for standard spec.
- 15,000 litres of recycling as standard, larger options available on request or simply upgraded to 35,000 litre Rhino Multi tanks if required.
- At 2.5m the side screens are the highest of any standard wheelwash in production in the world and maximise water retention. Galvanized option available.
- Mobile unit able to be re-located on site in one day.
- Easy to clean 1-tank, directional settlement system.
- Wash Platform can be inset in the ground or truly surface mounted with no excavation required.
- Can be used with customers own settlement lagoons.
- The Rhino Compact is a fully adjustable, programmable system for changeable site conditions.
- All spraying products come with removable grids in the Wash Platform as standard. Wheelwash Ltd is the only company in the market to provide this essential feature.
- Flow-form covered tank for safety with optional handrail.
- 380 mm high wash platform provides a soft entry suitable for most vehicle types.
- Hassle free set up with delivery via Hiab crane truck.
- Heavy-duty steel construction.
- All Wheelwash Ltd products are designed and manufactured in Britain.

Product Specification

RHINO COMPACT



All Dimensions in Millimetres

Rhino Compact 4000

Main Components

Wash Platform	4000mm x 3500mm x 380mm 2205 Kgs 2650 Litres Capacity
Ramp (Each & Optional)	3000mm x 1000mm x 380mm 295 Kgs
Mobile Road (Each & Optional)	3000mm x 1000mm x 380mm 325 Kgs
Settlement Tank	6000mm x 2000mm x 1250mm 2150 Kgs 15000 Litres Capacity
Side Screens (Each)	4 Off 2500mm x 2000mm x 2mm 110 Kgs (each)

Power Supply Required

Mains Power	415v 63amp Supply D Type Circuit Breaker
Generator	30 kVA

Wash Pump Specification

Rating (kw)	9.4
Flow Rate (Ltr/ Min)	760
Pressure (bar)	3

Waste Pump Specification

Rating (kw)	5.2
Flow Rate (Ltr/ Min)	1440

Supply / Nozzles

Water Inlet Required	25mm or 50mm
Spray Nozzles	Up to 80

*All weights are approximate dry weights. Wheelwash Limited reserves the right to change detailed specifications from time to time. Drawings are to show indicative layouts only and are not to scale. Specifications are based on supply within the UK, please ask for details outside of this location. Specifications may vary when systems supplied as rental units.